



Tel: +44 (0) 1706 869777
E-mail: sales@desal.co.uk
Web: www.desal.co.uk

DOWEX™ UPCORE™ IF-62

An Inert Resin Specifically Designed for the UPCORE Packed Bed Counter-Current Regeneration System

Product	Type	Matrix	Functional group
DOWEX™ UPCORE™ IF-62	Inert	Polyethylene	None

Typical Physical and Chemical Properties

Particle size range	mm	2.5 - 4.0
Particle density	g/mL	0.96
Shipping weight**	g/L	620
	lbs/ft ³	38

Recommended Operating Conditions

- Maximum operating temperature 110°C (230°F)
- pH range 0 - 14
- Bed depth, min. 150 mm (6 in)
- Flow rates 5 - 60 m/h (2 - 24 gpm/ft²)

Typical properties and applications

DOWEX™ UPCORE™ IF-62 inert resin is supplied in spherical form. Its particle size is specifically selected for use in the UPCORE packed bed counter-current regeneration system. DOWEX UPCORE IF-62 resin has a density less than water which ensures it stays above the ion exchange resin bed.

During compaction and regeneration, DOWEX UPCORE IF-62 resin allows dirt and resin fragments to pass through while retaining the resin bed which protects the collector system against blockage.

Packaging

25 liter bags

** As per the backwashed and settled density of the resin, determined by ASTM D-2187.

DOWEX™ Ion Exchange Resins
For more information about DOWEX resins, call the Dow Water Solutions business:

North America: 1-800-447-4369
Latin America: (+55) 11-5188-9222
Europe: (+32) 3-450-2240
Pacific: +60 3 7958 3392
Japan: +813 5460 2100
China: +86 21 2301 9000
<http://www.dowwatersolutions.com>

Warning: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

Notice: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

