



Tel: +44 (0) 1706 869777
 E-mail: sales@desal.co.uk
 Web: www.desal.co.uk

Introduction

AMBERLITE™ IRA67

Industrial Grade Weak Base Anion Exchanger

AMBERLITE IRA67 resin is a weak base anion exchange resin with a gel type acrylic matrix. It has a high capacity, excellent physical stability, fast kinetics, outstanding resistance to organic fouling and basicity higher than that of polystyrenic weak base resins.

The flexible acrylic structure of AMBERLITE IRA67 resin allows for effective adsorption and desorption of naturally occurring organic molecules, such as humic and fulvic acids, that are present in many water supplies.

Properties

Physical form	Translucent white spherical beads
Matrix	Crosslinked acrylic gel structure
Functional group	Tertiary amine
Ionic form as shipped	Free Base (FB)
Total exchange capacity	≥ 1.60 eq/L (FB form)
Moisture holding capacity	56 to 64 % (FB form)
Shipping weight	700 g/L
Particle Size	
Uniformity coefficient	≤ 1.80
Harmonic mean size	0.500 – 0.750 mm < 0.300 mm 3.0 % max
Reversible swelling	FB → Cl ⁻ ≤ 30 %

Suggested Operating Conditions

Maximum operating temperature	60 °C
Minimum bed depth	700 mm
Service flow rate	5 to 40 BV*/h
Regeneration	
Regenerant	NaOH
Level	130 % of ionic load
Concentration	2 to 4 %
Minimum contact time	30 minutes
Slow rinse	2 BV at regeneration flow rate
Fast rinse	8 to 16 BV at 10 BV/h

Hydraulic Characteristics

AMBERLITE IRA67 resin gives a pressure drop of about 18 kPa/m bed depth per 10 m/h at 15 °C. A backwash flow rate of 4 m/h gives a bed expansion of about 65 % at 15 °C.

For more information about DOW™ resins, call the Dow Water & Process Solutions business:

North America: 1-800-447-4369
 Latin America: (+55) 11-5188-9222
 Europe: +800-3-694-6367
 Italy: +800-783-825
 South Africa: +0800 99 5078
 Pacific: +8007776 7776
 China: +400 889-0789

<http://www.dowwaterandprocess.com>

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

